



DETAILED DESCRIPTION OF THE INVENTION.

In reference to Figures 1, and 2, the inside base 1 of a longitudinal side of a vehicle canopy or cover 2 is affixed to the top side of the truck bed 3 by a series of hinges 4 or a continuous hinge, all of which will maintain stability of the cover when lifting, closing, or in the open or closed position. In reference to Figure 1, the top flange of the hinge 4 is secured to the bottom of the canopy or cover side in a safe and appropriate manner. In reference to Figure 2, the end of the bottom flange of hinge 4 is bent at a 90 degree angle downward in order to secure the hinge to the top inside portion of the truck bed. This is done to accommodate a safe and easy method of attaching the canopy or lid to the vehicle.

In reference to Figure 3, the mechanical lift system is comprised of two parts. The first part is comprised of a base plate 5, which is preferably affixed to the top of a vehicle wheel well 6, and an upright arm 7 which is permanently attached to the base plate 5. The upright arm 7 is then attached to the top inside of the truck bed 3 via a moveable plate and sleeve 9 which is attached to the upright arm 7. Again, in reference to the base plate 5, a pivotal point 10 is attached to the base plate to accommodate the base of the power pack 11 used. In addition, the top of the upright arm 7 has also a pivotal point 12.

The second part of the mechanical lift system is the lift arm mechanism. Again, in reference to Figure 3, it is comprised of a lift arm 13 that is attached to pivotal point 12, and follows the upward contour of the canopy 2 to the cover ceiling. It then follows adjacent to the canopy ceiling in a parallel manner to the opposite side of the canopy ceiling to pivotal point 14. In addition, the lift arm 13 has a guide arm 15 with a pivotal point 16 at its end. Pivotal point 16 is the connection point for the top end of the power lift 11. Also attached to the guide arm 15, is a support arm 17 which also attaches to the upper portion of the lift arm 13. The lift arm mechanism continues with a down arm 18 connected to pivotal point 14 and follows downward the contour of the canopy side and connects with pivotal point 19 which is on

inside base cover plate 20. The inside cover base plate 20 is attached to the canopy inside cover base 21.

A heavy gauge wire (12) should be used to connect the power pack 11 to the vehicle battery through an ON-OFF-ON 3 -way toggle (intermittent rocker) switch. A 20 amp fuse should be placed on line between the battery and the toggle switch. This switch may be placed where it is most convenient to the customer.

The novel of this operation is the fact that it is simple and uncomplicated. We are using a structure (the canopy) that was intended to be a rigid on a truck box, to be opened and closed at will, thus allowing complete access to the truck bed and free access to all cargo you haul eg: fuel tanks, service lubricants, tools, miscellaneous equipment. When using this lift arm, the canopy is automatically secured while in the down position due to the character of the actuator used.